



## ZEUS EV charger

ZEUS-A7-ST/ZEUS-A11-ST

### Product Features



Overcurrent Protection



Short Circuit Protection



Leakage Protection



Lightning Protection



Undervoltage Protection



Overvoltage Protection



Waterproof Protection









Flame Retardant Protection



# Specification



Model	ZEUS-A11-ST	ZEUS-A7-ST
Rated voltage	AC400V (50/60Hz)	AC230V (50/60Hz)
Rated Ampere	16A	32A
Rated power	11kW	7kW
Wire	Three phase (3P+N+PE)	Single phase (P+N+PE)
Ingress Protection	Ip65	
Installation Options	Column / Wall mounted	
Colour	White	
Weight	5kg	
Dimension (MM)	190*110*320MM	
Operating temperature	-40°C to 60°C	-40°C to 60°C/50°C to 60°C(16A)
Humidity	5-95%humidity	
Altitude	≤2.0m	
Charging Cable Length	3.5M	
Environmental requirements	Meet ROHS2.0 requirements	


\*Conditions apply, refer to FelicityESS Warranty Letter.


## Status Indicator Light

Green breathing lamp Online Idle	Green all bright Online prepare	Yellow breathing lamp reserved	Yellow breathing lamp Charging suspension	Red all bright Disable	White water lamp Upgrading
					

Purple breathing lamp Offline Idle	Purple all bright Offline prepare
	

Green flashing End of charging	Red flashing Error
	

Purple water lamp If the temperature of the charging pile is too high, the derating charging will turn into a purple water lamp	
---	---

Green water lamp In the Charging The higher the charging current, the faster the rhythm of the status indicator	
---	---